

CONCRETE COATING COMPARISON

Find out how AMAZING FLOORS PRODUCTS™ compare to epoxy garage floor coatings.

FLOOR COATING COMPARISON	AMAZING FLOORS™	EPOXIES
Odor	Very low	Low
Product Flexibility	High	No
Primer Required	No	Yes
Bonding Characteristics	Deep penetration within	Topical surface bond
Dry mL Thickness	15 mL	15 mL
Number of Coats	3	2-3
Decorative Broadcast Material	Vinyl flakes colored	Vinyl flakes colored
Duration of Work up to 650ft	1 day	3 days
Return to Service - Foot Traffic	6 hours	24 hours
Return to Service - Vehicle Traffic	24 hours	4-7 days
Volatile Organic Compounds (VOCs)	Ultra low	Low
100% Environmentally Friendly	Yes	Yes
Vertical Surfaces and Outer Edge	Yes	No
Hot Tire Pick Up Resistance	Yes	No
Salt Stain Resistance	Yes	Moderate
Abrasion Resistance	Extremely High	Moderate
Chemical Resistance	Extremely high	Moderate
Applications	Indoor/outdoor	Indoor (Will yellow outdoor)
Application Temperature	-30°C to 40°C	10°C to 30°C
Chemical Reaction Product Mix Ratio	1:1	2:1
Pot Life	15 minutes	60 minutes
Concrete Preparation Method	Diamond grinding	Diamond grinding
Crack/Spall Repair Required	Yes	Yes
Ideal Applications	Garages, mechanic shops, basements, patios, verandas, showrooms, restaurants, walkways, pool decks, decorative applications	Industrial space, commercial space, very large spaces, mechanic shops, warehouses, containment areas, non-decorative